

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

| APPLICATION NO. | F | ILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|----------------------------------|---------------|------------|----------------------|------------------------|------------------|
| 10/693,606 | 06 10/27/2003 | | Wolfgang Drahm | | 6460 |
| 23364 | 7590 | 12/14/2005 | | EXAM | INER |
| BACON & | | • | BELLAMY, TAMIKO D | | |
| 625 SLATERS LANE FOURTH FLOOR | | | | ART UNIT | PAPER NUMBER |
| ALEXANDRIA, VA 22314 | | | 2856 | | |
| | | | | DATE MAILED: 12/14/200 | 5 |

Please find below and/or attached an Office communication concerning this application or proceeding.

| | Application No. | Applicant(s) |
|---|--|--|
| | 10/693,606 | DRAHM ET AL. |
| Office Action Summary | Examiner | Art Unit |
| | Tamiko D. Bellamy | 2856 |
| The MAILING DATE of this communica eriod for Reply | tion appears on the cover sheet w | ith the correspondence address |
| • • | | ONTH(S) FROM |
| A SHORTENED STATUTORY PERIOD FOR THE MAILING DATE OF THIS COMMUNICA - Extensions of time may be available under the provisions of 3 after SIX (6) MONTHS from the mailing date of this communic - If the period for reply specified above is less than thirty (30) d - If NO period for reply is specified above, the maximum statute - Failure to reply within the set or extended period for reply will, Any reply received by the Office later than three months after earned patent term adjustment. See 37 CFR 1.704(b). | ATION. 17 CFR 1.136(a). In no event, however, may a recation. ays, a reply within the statutory minimum of third properties of the prope | reply be timely filed by (30) days will be considered timely. ITHS from the mailing date of this communication. BANDONED (35 U.S.C. § 133). |
| tatus | | |
| 1) Responsive to communication(s) filed of | on 9/2/05 | |
| , | ☐ This action is non-final. | |
| 3)☐ Since this application is in condition for | _ | ers, prosecution as to the merits is |
| closed in accordance with the practice | under Ex parte Quayle, 1935 C.D |). 11, 453 O.G. 213. |
| isposition of Claims | | |
| 4)⊠ Claim(s) <u>11-45</u> is/are pending in the ap | polication | |
| 4a) Of the above claim(s) is/are | | |
| 5) Claim(s) is/are allowed. | | |
| 6) Claim(s) 11,12,18,20,21,23-25,34-38,4 | 0 and 42-45 is/are rejected. | |
| 7) Claim(s) <u>13-17,19,22, 26-33, 39, and 4</u> | 1 is/are objected to. | |
| 8) Claim(s) are subject to restrictio | n and/or election requirement. | |
| pplication Papers | | |
| 9)☐ The specification is objected to by the E | xaminer. | |
| 10) The drawing(s) filed on is/are: a |) ☐ accepted or b) ☐ objected to | by the Examiner. |
| Applicant may not request that any objection | | |
| Replacement drawing sheet(s) including the | | |
| 11) The oath or declaration is objected to by | y the Examiner. Note the attached | d Office Action or form PTO-152. |
| riority under 35 U.S.C. § 119 | | |
| 12) Acknowledgment is made of a claim for a) All b) Some * c) None of: | foreign priority under 35 U.S.C. § | 3 119(a)-(d) or (f). |
| Certified copies of the priority do | | |
| | | |
| 2. Certified copies of the priority do | | received in this National Stage |
| 3. Copies of the certified copies of | | |
| • | Bureau (PCT Rule 17.2(a)). | |

U.S. Patent and Trademark Office PTOL-326 (Rev. 1-04)

6) Other: ____.

4) Interview Summary (PTO-413)
Paper No(s)/Mail Date.

5) Notice of Informal Patent Application (PTO-152)

Paper No(s)/Mail Date _

1) X Notice of References Cited (PTO-892)

2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Application/Control Number: 10/693,606 Page 2

Art Unit: 2856

DETAILED ACTION

1. Amendment dated 9/2/05 has been received and entered. Claims 11-45 are currently pending.

Claim Objections

- 2. Claims 28, 33, 36, 37, and 38 are objected to because of the following informalities:
 - a. Claim 28, line 1, change "in the foregoing claim" to clam 25 --.
 - b. Claim 33, line 1, change "in the foregoing claim" to clam 25 --.
 - c. Claim 36, line 1, change "in the foregoing claim" to clam 25 --.
 - d. Claim 37, line 1, change "in the foregoing claim" to clam 25 --.
 - e. Claim 38, line 1, change "in the foregoing claim" to clam 25 --.

Appropriate correction is required.

Claim Rejections - 35 USC § 102

- (a) the invention was known or used by others in this country, or patented or described in a printed publication in this or a foreign country, before the invention thereof by the applicant for a patent.
- (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.
- 3. Claims 11, 12, 18, 21, 23, 25, 34-37, 40, 42, 43, and 45 are rejected under 35
- U.S.C. 102(a) as being anticipated by Reading et al. (2002/0026822).

Re claim 11, as depicted in figs. 1-3, Reading et al. incorporates reference (6,085,582) (See Pg. 5, par. 37), which discloses a sensor (e.g., mass flow meter 36) mounted in a wall of a vessel for holding or conveying a process medium (See ref. '582). Reading et al. discloses an electronics case (e.g., housing 20) for meter electronics, which is mechanically, particularly rigidly coupled to the sensor (e.g., mass flow meter 36) (See fig. 1 of ref. '582). As depicted in fig. 1, Reading et al. incorporates reference (6,085,582), which discloses the electronics case (See, '582, e.g., analyzer 28) is intermittently subjected to vibrations transmitted via the sensor (e.g., ultrasonic flow meter 36, See ref. '582, Col. 6, lines 46-58). As depicted in fig. 3, Reading et al. discloses that in order to reduce amplitudes of possible vibrations of the electronics case, a vibration absorber (e.g., dampers 32) which is vibrated at least intermittently in order to dissipate vibrational energy taken into the electronics case (e.g., housing 20) is affixed to

Re claim 12, as depicted in figs. 2 and 3, Reading et al. discloses that vibration absorber (e.g., dampers 32) is positioned at a distance between the electronic case (e.g., housing 20) and the sensor (See ref. 582,e.g., ultrasonic flow meter 36).

a wall of the electronic case (e.g., housing 20) (See Pg. 5, par. 38).

Re claim 18, as depicted in fig. 3, Reading et al. discloses that the vibration absorber (e.g., dampers 32) is disposed within the electronics case (e.g., housing 20).

Re claim 21, Reading et al. incorporates reference '582, which discloses that the process meter is an ultrasonic flow meter (Pg, 5, par. 37; See ref'582, Col. 6, lines 46-58).

Re claim 23, Reading et al. incorporates reference '582, which discloses the sensor (e.g., ultrasonic flow meter 36) is mounted in a pipe (e.g., dilute mixture duct 22) (See ref. '582 figs. 1-4).

Re claim 25, as depicted in figs. 1-3, Reading et al. incorporates reference (6,085,582) (See Pg. 5, par. 37), which discloses a sensor (e.g., mass flow meter 36) mounted in a wall of a vessel for holding or conveying a process medium (See ref. '582). Reading et al. discloses an electronics case (e.g., housing 20) for meter electronics, which is mechanically, particularly rigidly coupled to the sensor (e.g., mass flow meter 36) (See fig. 1 of ref. '582). As depicted in fig. 1, Reading et al. incorporates reference (6,085,582), which discloses the electronics case (See, '582, e.g., analyzer 28) is intermittently subjected to vibrations. As depicted in fig. 3, Reading et al. discloses that the vibration absorber (e.g., dampers 32) for reducing amplitudes of vibrations of the electronics case is located within the electronic case (e.g., housing 20) (See Pg. 5, par. 38).

Re claim 34, as depicted in fig. 3, Reading et al. discloses that the vibration absorber (e.g., dampers 32) is affixed to a wall of the electronics case (e.g., housing 20).

Re claims 36 and 37, as depicted in figs. 2 and 3, Reading et al. discloses that vibration absorber (e.g., dampers 32) is positioned at a distance between the electronic case (e.g., housing 20) and the sensor (See ref. 582,e.g., ultrasonic flow meter 36).

Re claim 37, Reading et al. discloses a vibration absorber (e.g., vibration damping means 32), which inherently includes a plastic body affixed to the wall of the electronics case (e.g., housing 20).

Re claim 40, Reading et al. incorporates reference (6,085,582), which discloses the electronics case (e.g., analyzer 28) is rigidly coupled the sensor (e.g., ultrasonic flow meter 36) (See ref. '582, fig. 1).

Re claim 42, as depicted in fig. 1, Reading et al. incorporates reference (6,085,582), which discloses the electronics case (See, '582, e.g., analyzer 28) is intermittently subjected to vibrations transmitted via the sensor (e.g., ultrasonic flow meter 36, See ref. '582, Col. 6, lines 46-58).

Re claim 43, Reading et al. incorporates reference '582, which discloses the sensor (e.g., ultrasonic flow meter 36) is mounted in a pipe (e.g., dilute mixture duct 22) (See ref. '582 figs. 1-4).

Re claim 45, Reading et al. incorporates reference '582, which discloses that the process meter is an ultrasonic flow meter (Pg, 5, par. 37; See ref'582, Col. 6, lines 46-58).

4. Claims 11, 12, 18, 21, 23, 25, 34-37, 40, 42,43, and 45 are rejected under 35 U.S.C. 102(e) as being anticipated by Reading et al. (2002/0026822).

Re claim 11, as depicted in figs. 1-3, Reading et al. incorporates reference (6,085,582) (See Pg. 5, par. 37), which discloses a sensor (e.g., mass flow meter 36) mounted in a wall of a vessel for holding or conveying a process medium (See ref. '582). Reading et al. discloses an electronics case (e.g., housing 20) for meter electronics, which is mechanically, particularly rigidly coupled to the sensor (e.g., mass flow meter 36) (See fig. 1 of ref. '582). As depicted in fig. 1, Reading et al. incorporates reference (6,085,582), which discloses the electronics case (See, '582, e.g., analyzer 28) is

intermittently subjected to vibrations transmitted via the sensor (e.g., ultrasonic flow meter 36, See ref. '582, Col. 6, lines 46-58). As depicted in fig. 3, Reading et al. discloses that in order to reduce amplitudes of possible vibrations of the electronics case, a vibration absorber (e.g., dampers 32) which is vibrated at least intermittently in order to dissipate vibrational energy taken into the electronics case (e.g., housing 20) is affixed to a wall of the electronic case (e.g., housing 20) (See Pg. 5, par. 38).

Re claim 12, as depicted in figs. 2 and 3, Reading et al. discloses that vibration absorber (e.g., dampers 32) is positioned at a distance between the electronic case (e.g., housing 20) and the sensor (See ref. 582,e.g., ultrasonic flow meter 36).

Re claim 18, as depicted in fig. 3, Reading et al. discloses that the vibration absorber (e.g., dampers 32) is disposed within the electronics case (e.g., housing 20).

Re claim 21, Reading et al. incorporates reference '582, which discloses that the process meter is an ultrasonic flow meter (Pg, 5, par. 37; See ref'582, Col. 6, lines 46-58).

Re claim 23, Reading et al. incorporates reference '582, which discloses the sensor (e.g., ultrasonic flow meter 36) is mounted in a pipe (e.g., dilute mixture duct 22) (See ref. '582 figs. 1-4).

Re claim 25, as depicted in figs. 1-3, Reading et al. incorporates reference (6,085,582) (See Pg. 5, par. 37), which discloses a sensor (e.g., mass flow meter 36) mounted in a wall of a vessel for holding or conveying a process medium (See ref. '582). Reading et al. discloses an electronics case (e.g., housing 20) for meter electronics, which is mechanically, particularly rigidly coupled to the sensor (e.g., mass flow meter 36) (See

Application/Control Number: 10/693,606

Art Unit: 2856

fig. 1 of ref. '582). As depicted in fig. 1, Reading et al. incorporates reference (6,085,582), which discloses the electronics case (See, '582, e.g., analyzer 28) is intermittently subjected to vibrations. As depicted in fig. 3, Reading et al. discloses that the vibration absorber (e.g., dampers 32) for reducing amplitudes of vibrations of the electronics case is located within the electronic case (e.g., housing 20) (See Pg. 5, par. 38).

Page 7

Re claim 34, as depicted in fig. 3, Reading et al. discloses that the vibration absorber (e.g., dampers 32) is affixed to a wall of the electronics case (e.g., housing 20).

Re claims 36 and 37, as depicted in figs. 2 and 3, Reading et al. discloses that vibration absorber (e.g., dampers 32) is positioned at a distance between the electronic case (e.g., housing 20) and the sensor (See ref. 582,e.g., ultrasonic flow meter 36).

Re claim 37, Reading et al. discloses a vibration absorber (e.g., vibration damping means 32), which inherently includes a plastic body affixed to the wall of the electronics case (e.g., housing 20).

Re claim 40, Reading et al. incorporates reference (6,085,582), which discloses the electronics case (e.g., analyzer 28) is rigidly coupled the sensor (e.g., ultrasonic flow meter 36) (See ref. '582, fig. 1).

Re claim 42, as depicted in fig. 1, Reading et al. incorporates reference (6,085,582), which discloses the electronics case (See, '582, e.g., analyzer 28) is intermittently subjected to vibrations transmitted via the sensor (e.g., ultrasonic flow meter 36, See ref. '582, Col. 6, lines 46-58).

Application/Control Number: 10/693,606

Art Unit: 2856

Re claim 43, Reading et al. incorporates reference '582, which discloses the sensor (e.g., ultrasonic flow meter 36) is mounted in a pipe (e.g., dilute mixture duct 22) (See ref. '582 figs. 1-4).

Page 8

Re claim 45, Reading et al. incorporates reference '582, which discloses that the process meter is an ultrasonic flow meter (Pg, 5, par. 37; See ref'582, Col. 6, lines 46-58).

Claim Rejections - 35 USC § 103

- 5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 6. Claims 20, 24, 38, and 44 are rejected under 35 U.S.C. 103(a) as being unpatentable over Reading et al. (2002/0026822).

Re claims 20 and 38, as depicted in fig.1, Reading et al. discloses the vibration absorber (e.g., dampers 32) is affixed to the wall of the electronics case (e.g., housing 20). While, Reading et al. does not specifically disclose that the vibration absorber is affixed to the electronic casing **particularly with adhesive**, as depicted in fig. 3, Reading et al. discloses that the vibration absorber (e.g., dampers 32) is mounted within a groove of the electronic case (e.g., housing 20) which is formed by joining two potions of the electronic case (e.g., combination of first end plate (24) and shell (22)) (See Pg. 5, par 37, lines 3-5) together. On having ordinary skill in the art knows that using an adhesive as a

Application/Control Number: 10/693,606

Art Unit: 2856

Page 9

means for affixing a component, requires minor skill. Therefore, to employ Reading et al. on an adhesive for affixing a vibration absorber to an electronic case would have been obvious to one of ordinary skill in the art at the time of the invention since this reference explicitly teaches a process meter, which includes a vibration absorber affixed with the wall of an electronic case.

Re claims 24, and 44, Reading et al. discloses that the sensor is mounted within a wall of a pipe. While Reading et al. does not specifically discloses that the sensor is mounted in a wall of a tank, the device of reading would operate equally as well in a tank as opposed to a pipe. The court held in , In re Pearson, 494 F.2d 1399, 181 USPQ 641 (CCPA 1974); In re Yanush, 477 F.2d 958, 177 USPQ 705 (CCPA 1973); In re Finsterwalder, 436 F.2d 1028, 168 USPQ 530 (CCPA 1971); In re Casey, 370 F.2d 576, 152 USPQ 235 (CCPA 1967); In re Otto, 312 F.2d 937, 136 USPQ 458 (CCPA 1963); Ex parte Masham, 2 USPQ2d 1647 (BdPatApp & Inter 1987), that a recitation with respect to the manner in which an apparatus is intended to be employed does not impose any structural limitation upon the claimed apparatus which differentiates it from a prior art reference disclosing the structural limitations of the claim. Therefore, to employ Reading et al. on a mounting a sensor in a wall of a tank would have been obvious to one of ordinary skill in the art at the time of the invention since this reference explicitly teaches a process meter mounted in the wall of a pipe.

Application/Control Number: 10/693,606 Page 10

Art Unit: 2856

Allowable Subject Matter

7. Claims 13-17, 19, 22, 26-33, 39, and 41 are objected to as being dependent upon a rejected base claim 11, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

Response to Remarks

8. Applicant's arguments with respect to claims 11, 12, and 18 have been considered but are moot in view of the new ground(s) of rejection. It is the examiners position that claims 11, 12, 18, 20, 21, 23-25, 34-38, 40, 42-45 are not patentable in view of the newly applied art of Reading et al. (2002/0026822).

Conclusion

9. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Tamiko D. Bellamy whose telephone number is (571) 272-2190. The examiner can normally be reached on Monday - Friday 7:30 AM to 3:30 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Hezron Williams can be reached on (571) 272-2208. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Tamiko Bellamy

(-B.) December 13, 2005

HEZRON WILLIAMS

SUPERVISORY PATENT EXAMINER TECHNOLOGY CENTER 2800